



SIGNS, SIGNALS & BARRICADES PROTECTION PROGRAM

Climate Engineers and Climate River Valley follow the OSHA Safety and Health Standards code 29 CFR 1926.200. The following items should be used as warnings for hazards that could be encountered at the worksite.

1. **SIGNS, SIGNALS AND BARRICADES** shall be placed so as to provide appropriate warning to all affected personnel, provide appropriate levels of protection from hazards, and shall be visible at all times while work is being performed or while there is potential exposure to the hazard by any person.
2. **SIGNS, SIGNALS AND BARRICADES** shall be removed promptly after the hazard is no longer present.
3. These items shall be constructed of materials which are able to withstand the types, and duration of exposures present. They also shall be placed so as to provide sufficient *advanced warning* to all affected personnel.
4. **DANGER SIGNALS** shall be used only where an immediate hazard exists.
5. **CAUTION SIGNALS** shall be used only to warn against potential hazards, or to caution against unsafe practices.
6. **TRAFFIC SIGNALS** shall be posted at all points of hazard, and shall conform to ANSI specification D6.1-1971: Uniform Traffic Control Devices for Streets and Highways.
7. **ACCIDENT PREVENTION TAGS** shall be used only as temporary means of identifying, and warning against existing hazards such as defective tools or equipment. The ~~DO~~ NOT OPERATE+tag is an example of such a device.
8. Where signs, signals, or barricades alone are insufficient to protect against existing or potential hazards a flagman or signalman shall be assigned to direct traffic away from the hazard and control the area. The signaling shall conform to ANSI specifications D6.1-1971, and the person assigned these duties shall be appropriately trained, clothed in orange or red warning garment, and if necessary due to darkness shall be provided appropriate reflective signs and lights.
9. **NO EMPLOYEE** shall deface, remove, or move a warning sign, signal or barricade unless they insure that the hazard for which it was placed no longer exists.

BARRICADE COLOR CODES: YELLOW . WARNING! Proceed with caution.
RED . DANGER . STOP! Enter only if authorized.

OUR GOAL IS **ZERO** INJURIES IN THE WORKPLACE